

ICMsystem Versatile PD measurement system

技术咨询和询价：010-68940148



- Modular partial discharge test set for a range of high voltage assets
- Versatile equipment options
- Allows PD and RIV acceptance tests according to international standards
- Parallel recording of PD activity to test complex assets
- Up to ten parallel measurement channels (multi-channel system)

康高特-PDSG ICMsystem局放检测仪 DESCRIPTION

The ICMsystem is a universal Partial Discharge (PD) device which can be flexibly used by adjusting versatile features and accessories to fit your testing purpose. It has the highest grade of modularity and versatility, therefore, it can be used for laboratory tasks (QAQC) and on-site testing (on-line and off-line) for all your assets.

All controls and displays are accessible on the screen of a PC via a graphical interface, a so-called 'virtual instrument'.

The ICMsystem is primarily intended for the measurement of the following assets:

- Transformers
- Rotating machines
- Gas-insulated switchgear (GIS)
- Air-insulated switchgear (AIS)
- HV and EHV cables
- HV components such as bushings, insulators, and capacitors

ICMsystem YOUR ADVANTAGES

- Flexibly configurable for all assets by changing the accessories
- Time saving due to simultaneous PD measurements with optional multi-channel system
- Easy analysis of your results due to clear and understandable PD patterns

康高特-PDSG ICMsystem局放检测仪 FEATURES AND OPTIONS

As a multi-purpose PD measurement instrument, the ICMsystem offers the following features and options:

- PD spectrum analysis
- High voltage measurement (HVM)
- Synchronisation frequency from VLF to 510 Hz
- DC measurement mode
- DAkkS calibrated voltage measurement and PD calibrator
- Acoustic fault location
- PD fault location on cables
- Can be equipped with up to ten channels for parallel measurement of PD and RIV in real-time
- Effective noise gating for blocking phase-stable or phase-independent noises
- Radio interference voltage (RIV) measurement
- High-resolution PD patterns
- Available with pre-installed PCs or notebooks

TECHNICAL DATA

Acquisition unit

Mains supply	90–264 V AC, 47–440 Hz (automatic)
Line fuse	2 A (time-lag) (ICMsystem with up to four channels) 3.15 A (time-lag) (ICMsystem with five to ten channels)
Power requirements	ca. 110 VA max.
Operation	Remote-controlled via ICMsystem software
Operation temperature	0–40 °C (non-condensing)
Input impedance (AMP IN)	50 Ω 50 pF
A/D converter (PD)	12 bits, compressed into 8 bits (unipolar) / ±7 bits (bipolar)
Size (W x H x D, excl. BNC connectors)	236 x 133 x 300 mm ³ (ICMsystem with up to four channels) 450 x 133 x 300 mm ³ (ICMsystem with five to ten channels)
Weight	Approx. 6.9–9 kg

Standard PD mode

Lower cut-off (-6 dB)	40, 80, or 100 kHz (software-controlled)
Upper cut-off (-6 dB)	250, 600, or 800 kHz (software-controlled)
Input sensitivity	< 500 μV RMS/5 pC (without preamplifiers)
Gain range	4, 8, 10, 20 ..., 200, 400, 800
PD pattern resolution (x-y-z)	8 x 8 x 16 bits

Preamplifiers

Input impedance:

RPA1/RPA1D/RPA1G/RPA4	10 kΩ 50 pF
RPA1L / RPA1H	1 kΩ 50 pF
FCU2	50 Ω 50 pF

Input sensitivity:

RPA1/RPA1D/RPA1G/RPA4	< 50 μV RMS/0.03 pC
RPA1L	< 15 μV RMS/0.02 pC
RPA1H	< 40 μV RMS/0.05 pC
RPA2	< 800 μV RMS/1 pC
RPA3	< 2 μV RMS
FCU2	< 200 μV RMS (46 dBμV)

Bandwidth:

RPA1/RPA1D/RPA1G/RPA4	40–800 kHz
RPA1L/RPA1H	40 kHz–20 MHz
RPA2	2–20 MHz
RPA3	200 MHz–1 GHz
FCU2	100 MHz–1800 MHz

Synchronisation / HVM

Synchronisation frequency	20–510 Hz (automatic) / 0.02–510 Hz (manual)
Maximum voltage	200 V _{peak} (140 V RMS), 100 V RMS nom.
Input impedance	10 MΩ
A/D converter	± 15 bits
Measurement uncertainty	Typ. < 1.5 %



TECHNICAL DATA

Spectrum function

Input sensitivity	< 5 μV RMS/0.5 pC (270 kHz bandwidth) < 1 μV RMS/2 pC (9 kHz bandwidth)
Maximum input voltage	120 mV RMS (300 kHz bandwidth, SPEC mode) 5 mV RMS (9 kHz bandwidth, SPEC mode) 2.5 mV RMS (RIV measurement)
Frequency range	10 kHz–10 MHz (in steps of 10 kHz)
Bandwidth	9 kHz or 270 kHz
Measurement uncertainty	Typ. < 5 %

PD location within cables

Trigger	0–100 % of input signal (in steps of 3.125 %)
A/D converter	± 7 bits
Samples	100 Msamples/s ($T_{\text{sample}} = 10$ ns)
Reduced sample rates	50 MS, 25 MS
Displayed time window	200 ... 8000 samples (2 ... 80 μs @ 100 MS / 8 ... 320 μs @ 25 MS)
Specimen cable length	10 to 5000 m, for 80 μs and $v_c = 140$ m/ μs (Please note: Localisation at cables with a length > 3000 m not possible because of pulse attenuation)
Localisation precision	1 m + 0.1 % of cable length

Acoustic fault location

Trigger	0–100 % of input signal (in steps of 3.125 %)
A/D converter	± 7 bits
Samples	100 Msamples/s ($T_{\text{sample}} = 10$ ns)
Reduced sample rates	50 MS, 25 MS, 10 MS, 5 MS, 1 MS
Displayed time window	200 ... 8000 samples (2 ... 80 μs at 100 MS / 200 ... 8000 μs at 1 MS)
Maximum location distance	11.2 m, for 8000 μs and $v_{\text{oil}} = 1400$ m/s

Available communication interfaces

USB

GPIB

LAN

ICMsystem Versatile PD measurement system

ACCESSORIES

To perform a measurement, the ICMsystem requires accessories, depending on your testing purpose and environment. The following accessories are recommended:

- Preamplifiers of RPA and FCU series
- Coupling capacitors
- Quadrupoles
- Current transformers
- Sensors
- Bushing adapters
- Disturbance antennas
- DAkKS certified calibration impulse generators
- Robust transportation case

For more details, as well as ordering information on our accessories, please refer to our accessories catalogue.



ORDERING INFORMATION

Product	Order no.	Options	Order no.
ICMsystem Generation 5, 1/2 19 inch housing	PX10026	Spectrum analysis (incl. RIV measurement)	PX10028
ICMsystem Generation 5, 19 inch housing	PX10030	PD fault location for cables	PX10029
Measurement plugin board	PX10027	IEEE488 communication interface (GPIB-USB)	PX90102
Cable set for ICMsystem with one channel	PX17006	Remote control computer system	PX90000
Cable set for ICMsystem with up to four channels	PX17059	Transportation case for instruments with up to four channels and accessories	PX18128
Cable set for ICMsystem with up to ten channels	PX17154	Transportation case for instruments with up to four channels and acoustic accessories	PX18122
Software		High transportation case for instruments with up to four channels and acoustic accessories	PX18126
Standard control software	PX19010	Transportation case for instruments with five to ten channels and accessories	PX18120
Multi-channel control software	PX19009		
Multi-channel control software for acceptance tests	PX19000		
ICMacoustic software for acoustic fault location	PX19008		

Set of measuring cables is NOT included with the instrument and must be ordered separately.